

Infrared Emitting Diode

红外线发射管


Module No : **JY9420-C5**

Lens Color : Water clear

1. General Description:

JY9420-C5 is a high output power GaAlAs infrared light emitting diode, mounted in a clear epoxy end looking package. It emits narrow band of radiation peaking at 940nm.

Dimensions



2. Features

- Ultra narrow beam angle
- Good linearity
- Capable of pulse operation
- High output power
- Low cost

3. Absolute Maximum Ratings

(Ta=25°C)

Parameter	Symbol	Ratings	Unit
Forward Current	I_F	100	mA
Pulse Forward current *1	I_{FP}	1	A
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	150	mW
Operating Temperature	T_{opr}	-25 ~ +70	°C
Storage Temperature	T_{stg}	-25 ~ +80	°C
Soldering Temperature *2	T_{sol}	260	°C



*1 Pulse width $\leq 100\mu\text{sec}$. Duty ratio = 0.01

*2 At the position of 2mm from the bottom of the package within 5 seconds.

4. Electro-optical Characteristics

(Ta=25°C)

Parameter	Symbol	Testing Conditions	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F=100\text{mA}$		1.4	1.7	V
Reverse Current	I_R	$V_R=5\text{V}$			10	μA
Radiant Intensity	P_o	$I_F=100\text{mA}$	50	130		mW/sr
Terminal Capacitance	C_t	$f=1\text{MHz}$		25		pF
Half Power Beam Angle	$\Delta\theta$			± 25		deg.
Peak Emission Wavelength	λ_p	$I_F=100\text{mA}$		940		nm
Spectral Bandwidth at 50%	$\Delta\lambda$	$I_F=100\text{mA}$		45		nm




Infrared Emitting Diode

红外线发射管


Module No :JY9420-C5

Lens Color : Water clear


Forward Current vs Forward Voltage




Spectral Distribution




Power Dissipation vs Ambient Temperature



Relative Output power vs Ambient Temperature



Relative Power vs Distance to Detector



Distance to Detector Test Conditions

