

SPECIFICATION

PART NO. : LT9F13-AH-UJE1
HIGH POWER AUTOMATIVE LED



Approved by

Checked by





Prepared by

Sam

Lian

Paul

Package Dimensions



Notes:

1. ALL DIMENSIONS ARE IN mm.
2. TOLERANCE IS ± 0.25 mm UNLESS OTHERWISE NOTED.

Description

| Part No. | LED Chip | | Lens Color |
|----------------|--------------|----------------|-------------|
| | Material | Emitting Color | |
| LT9F13-AH-UJE1 | AlGaInP/GaAs | Hyper Red | Water Clear |

Absolute Maximum Ratings at Ta=25

| Parameter | Symbol | Rating | Unit |
|---|-----------------------|-------------|------|
| Power Dissipation | P _D | 75 | mW |
| Reverse Voltage | V _R | 5 | V |
| D.C. Forward Current | I _f | 30 | mA |
| Peak Current(1/10Duty Cycle,0.1ms Pulse Width.) | I _f (Peak) | 100 | mA |
| Operating Temperature Range | T _{opr.} | -25 to +85 | |
| Storage Temperature Range | T _{stg.} | -40 to +100 | |
| Lead Soldering Temp. (1.6mm from body) for 5 seconds. | | 260 | |
| Electric Static Discharge Threshold (HBM) | | 300 | V |


Electrical and Optical Characteristics:

| Parameter | Symbol | Condition | Min. | Typ. | Max. | Unit |
|-------------------------|----------------|----------------------|------|------|------|------|
| Luminous Intensity | I _v | I _f =20mA | 2750 | 6900 | | mcd |
| Forward Voltage | V _f | I _f =20mA | | 2.1 | 2.5 | V |
| Peak Wavelength | λ _P | I _f =20mA | | 632 | | nm |
| Dominant Wavelength | λ _D | I _f =20mA | | 625 | | nm |
| Reverse Current | I _r | V _r =5V | | | 50 | μA |
| Viewing Angle | 2 1/2 | I _f =20mA | | 15 | | deg |
| Spectrum Line Halfwidth | Δλ | I _f =20mA | | 20 | | nm |


NOTE: THE DATAS TESTED BY IS TESTER.

Typical Electrical/Optical Characteristic Curves


(25 Ambient Temperature Unless Otherwise Noted)




Forward Current VS. Applied Voltage



Forward Current VS. Luminous Intensity



Ambient Temperature vs. Forward Current



Radiation Diagram

Precautions:

TAKE NOTE OF THE FOLLOWING IN USE OF LED

1. Temperature in use

Since the light generated inside the LED needs to be emitted to outside efficiently, a resin with high light transparency is used; therefore, additives to improve the heat resistance or moisture resistance (silica gel, etc) which are used for semiconductor products such as transistors cannot be added to the resin.

Consequently, the heat resistant ability of the resin used for LED is usually low; therefore, please be careful on the following during use.

Avoid applying external force, stress, and excessive vibration to the resins and terminals at high temperature. The glass transition temperature of epoxy resin used for the LED is approximately 120-130°C.

At a temperature exceeding this limit, the coefficient of linear expansion of the resin doubles or more compared to that at normal temperature and the resin is softened.

If external force or stress is applied at that time, it may cause a wire rupture.

2. Soldering

Please be careful on the following at soldering.

After soldering, avoid applying external force, stress, and excessive vibration until the products go to cooling process (normal temperature), <Same for products with terminal leads>

(1) Soldering measurements:

Distance between melted solder side to bottom of resin shall be 1.6mm or longer.

(2) Solder dip: Preheat: 90°C max. (Backside of PCB), Within 120 seconds

Solder bath: 250°C max. (Solder temperature), Within 5 seconds

(3) Soldering iron : 250°C max. (Temperature of soldering iron tip), Within 3 seconds

3. Insertion

Pitch of the LED leads and pitch of mounting holes need to be same

4. Others

Since the heat resistant ability of the LED resin is low, SMD components are used on the same PCB, please mount the LED after adhesive baking process for SMD components. In case adhesive baking is done after LED lamp insertion due to a production process reason, make sure not to apply external force, stress, and excessive vibration to the LED and follow the conditions below.


Baking temperature: 120°C max. Baking time: Within 60 seconds

If soldering is done sequentially after the adhesive baking, please perform the soldering after cooling down the LED to normal temperature.

ENCASED TYPE


TUBE:
QUANTITY: 60 PCS

PART NO :LTXXXX-XX
LOT :XXXXXXXXXX QTY'S :XXPCS BIN CODE:XX-XX



INNER BOX
QUANTITY: 126 tubes
TOTAL: 7560 PCS

| | | | | | |
|----------|--------------|------|------|------|-------|
| PART NO. | LXXXX-XX-XX | | | | |
| LOT NO. | XXXXXXXXXX | | | | |
| BIN CODE | Xx X | Xx X | Xx X | Xx X | TOTAL |
| QUANTITY | PCS | PCS | PCS | PCS | PCS |
| DATE | XXXX, XX, XX | | | | |



OUTER CARTON
QUANTITY: 4 BOX
TOTAL: 30,240 PCS

| | |
|-----------------|-------------|
| C/T NO. 箱 號 | XX |
| PART NO. 料 號 | LXXXX-XX-XX |
| QUANTITY 數 量 | PCS |
| N.W. 淨 重 | KGS |
| G.W. 毛 重 | KGS |
| REMARK 備 註 | |

