

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Note:

1. Material:


- 1.1 Insulator: P.B.T+30%G.F. UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Brass,t=0.30mm.

2. Specification:

- 2.1 Rated voltage and current:1.5A at 250V AC minimum.
- 2.2 Dielectric withstanding voltage: 500V AC/1 minute without breakdown.
- 2.3 Contact resistance:Before life test 30m ohm max,
After life tset 50m ohm max.
- 2.4 Insulation resistance:1000M ohm min.
- 2.5 Insertion force:35 Newtons maximum.
- 2.6 Extraction force:10 Newtons minimum.
- 2.7 Solderability:Terminal shall be immersed in flux before text,Then dip
in molten solder for 5±0.5 sec. At 245±5°C.

3. Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10u",15u",30u".
- 3.2 Shell: Nickel plated.



No.	Name	Q'ty	Material	Remarks & Thickness	Finish
3	Shell	1	Brass	T=0.30mm	Nickel Plated
2	Contact	8	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/Ivory

PART NO:		MATERIAL:		PART NAME:	
MODEL NO:		FINISH:		USB-A TYPE (F) 180°雙層焊線式有彈	
UNIT: mm	SIZE: A4	COLOR:		DWG NO: S/A-304	
TOLERANCE UNSPECIFIED		DR: 李霞		REV: A0	
x	±0.3	CHK:Kevin		SCALE: 2:1	
.xxx	±0.20	APP:Kent		SHEET: 1 of 1	
ANG.	±0.100	06/05/09		REV: A0	