

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

- Note:
- 1.Material:
- 1.1 Insulator:PA6T UL 94-V0 rated.
- 1.2 Contact: Phosphor bronze,t=0.25mm.
- 1.3 Shell: Brass,t=0.40mm.

- 2.Specification:
- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total mating force: 29.4 Newtons Max.
- 2.6 Total unmating force: 4.9 Newtons Min.
- 2.7 Temperature range: -55℃~+105℃

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 shell:Nickel or Tin plated.

3	Shell	1	Brass	T=0.40mm	Nickel or Tin Plated
2	Contact	5	Phosphor bronze	T=0.25mm	Gold Flashed
1	Housing	1	PA6T	UL 94-V0	Black/Ivory
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO:		MATERIAL:	
MODEL NO:		FINSH:	
UNIT: mm	SIZE: A4	COLOR:	
TOLERANCE UNSPECIFIED		PART NAME:	
.x	±0.3	MINIUSB-5PIN(F) B TYPE 90° DIP(四腳)	
.xx	±0.20		
.xxx	±0.100		
ANG.	±1°	APP:Kent '06/04/20	SCALE: 4:1
			SHEET: 1 of 1
			REV: A0

