







REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVSER	APPD

Note:

1.Material:

- 1.1 Insulator: L.C.P or PA46 UL 94-V0 rated.
- 1.2 Contact: Phosphor bronze,t=0.25mm.
- 1.3 Shell: Phosphor bronze,t=0.30mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Total mating force: 24.5 Newtons Max.
- 2.6 Total unmating force: 4.9 Newtons Min.
- 2.7 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10u",15u",30u".
- 3.2 Shell: Tin Plated.

No.	Name	Q'ty	Material	Remarks & Thickness	Finish
3	Shell	1	Phosphor bronze	T=0.30mm	Tin Plated
2	Contact	4	Phosphor bronze	T=0.25mm	Gold Flashed
1	Housing	1	L.C.P or PA46	UL 94-V0	Black/Ivory

PART NO:	MATERIAL:				
MODEL NO:	FINSH:				
UNIT: mm	SIZE: A4	COLOR:	PART NAME:		
TOLERANCE UNSPECIFIED		DR: 段林麗	MINI USB-4PIN(F)S.M.(mitsumi)		
.x	±0.3	CHK: Kevin	DWG NO:	S/A-330	REV: A0
.xx	±0.20	APP: Kent	SCALE: 6:1	SHEET: 1 of 1	
.xxx	±0.100				
ANG.	±1°				