

SD & MMC CARD

0.50±0.03

0.35

24.50

1.70

2.20

23.30

22.30

SW#2

SW#1

SW#3

0.15±0.03

0.40 A B-C B

0.15±0.03

0.70 A B-C B

8

7

6

5

4

3

2

1

9

2.31

5.50

15.81

16.31

17.11

18.61

34.3

0.15±0.03	0.40	A	B-C	B
0.15±0.03	0.70	A	B-C	B

SDAMB-012XXBXXX

LOGO

0: WITHOUT LOGO.

1: WITH KINGFONT LOGO.

1: WITH KING-FONT LOGO.
2: WITHOUT LOGO.& M/E.

0: TRAY.
1: TAPE REEL

NOTE:SD AND MMC FULL COMPATIBLE

DIMENSION IN mm [inch]

PROD. SPEC. 000010

TOLERANCE UNLESS OTHERWISE SPECIFIED

PN6, SPEC.

$X \pm 0.30$	$X \pm 1$
--------------	-----------

APPROVED *ND 8/2/00*

$.XX \pm 0.20$	$.X \pm$
----------------	----------

CHEN

 $\frac{XX \pm 0.10}{XX \pm}$

DRAW

CUSTOMER DRAWING

CARD CONNECTOR TYPE A

CUSTOMER DRAWING

FILE NO. KFP-019

DWG NO. SDAMB-012XXBXXX

A4 SIZE

PROJ:		SCALE:		2
-------	---	--------	---	---

A4

SCALE	2:1	REV	H
-------	-----	-----	---

Technical drawing of a mechanical assembly, showing two views: a front view (top) and a side view (bottom). The drawing includes dimensions for various components, including a central shaft with a diameter of 1.10 ± 0.05 , a central nut with a diameter of 0.08 A-B B , and a central bolt with a diameter of 0.08 A-B C . The drawing also shows a detail view of the central nut and bolt assembly, labeled "DETAIL A". The drawing is scaled at 2:1.

Dimensions and Tolerances:


- Overall length: 25.40 ± 0.05
- Overall width: 13.15
- Central shaft diameter: 1.10 ± 0.05
- Central nut diameter: 0.08 A-B B
- Central bolt diameter: 0.08 A-B C
- Top flange diameter: $\phi 1.20 \pm 0.03$
- Bottom flange diameter: $\phi 1.60 \pm 0.03$
- Top flange thickness: 1.625
- Bottom flange thickness: 2.80
- Top flange hole diameter: 0.20 ± 0.05
- Bottom flange hole diameter: 0.20 ± 0.05
- Top flange hole position: 2.70 ± 0.05
- Bottom flange hole position: 2.70 ± 0.05
- Top flange hole diameter: 0.20 ± 0.05
- Bottom flange hole diameter: 0.20 ± 0.05
- Top flange hole position: 2.70 ± 0.05
- Bottom flange hole position: 2.70 ± 0.05
- Top flange hole diameter: 0.20 ± 0.05
- Bottom flange hole diameter: 0.20 ± 0.05
- Top flange hole position: 2.70 ± 0.05
- Bottom flange hole position: 2.70 ± 0.05

Other Dimensions:


- Top flange hole diameter: 0.20 ± 0.05
- Bottom flange hole diameter: 0.20 ± 0.05
- Top flange hole position: 2.70 ± 0.05
- Bottom flange hole position: 2.70 ± 0.05
- Top flange hole diameter: 0.20 ± 0.05
- Bottom flange hole diameter: 0.20 ± 0.05
- Top flange hole position: 2.70 ± 0.05
- Bottom flange hole position: 2.70 ± 0.05

PC BOARD LAYOUT COMPONENT SIDE

WITHOUT CARD



CARD INSERTED
WRITE PROTECT : LOCK



CARD INSERTED
WRITE PROTECT : UNLOCK