



特点

- 引脚间距: 标准 2.54mm
- 引脚数量: 单排: 1~32个, 双排: 4~64个
- 触点数目可以按用户要求而定

电气特性

- 额定电流: 1 A
- 接触电阻: $\leq 20\text{ m}\Omega$
- 绝缘电阻: $\geq 5000\text{ M}\Omega$
- 耐电压: 500 V r.m.s

机械特性

- 插入力: $\leq 3.0\text{ N/pin}$ (用 0.64×0.64 的钢针)
- 拔出力: $\geq 0.2\text{ N/pin}$ (用 0.64×0.64 的钢针)
- 适用环境: $-55^{\circ}\text{C}\sim+125^{\circ}\text{C}$

1268 - XXX - XX - X

塑胶材料及颜色
(Insulator material and color)
1: 黑色(Black), PBT, UL94V-0

镀层代码 (Plating code)

代码 (Code)	定义 (Definition)
1	3 μm Sn
2	镀金(Au), CLASS I
3	镀金(Au), CLASS II
4	镀金(Au), CLASS III

排数 (Number of rows)

代码 (Code)	定义 (Definition)
1	单排 (Single row)
2	双排 (Double row)

长度代码 (Length code)

代码 (Code)	定义 (Definition) "A"
0	A=2.9

引脚数量 (Pin number)

代码 (Code)	定义 (Definition)
1~32	单排 (Single row)
4~64	双排 (Double row)

1268系列代码 (1268 Series)

Features

- Pitch: standard 2.54mm
- Contacts : 1 to 32 pins(single row),
4 to 64 pins(double row)
- Contacts can be ordered upon customer's request

Electrical

- Current rating: 1A
- Contact resistance: $\leq 20\text{ m}\Omega$
- Insulation resistance: $\geq 5000\text{ M}\Omega$
- Withstanding voltage: 500V r.m.s

Mechanical

- Insertion force: $\leq 3.0\text{ N/pin}$ (with steel pin 0.64×0.64)
- Extraction force: $\geq 0.2\text{ N/pin}$ (with steel pin 0.64×0.64)
- Operating temperature: $-55^{\circ}\text{C}\sim+125^{\circ}\text{C}$

