







REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.20mm.
- 1.3 Shell: Cold rolled steel,t=0.30mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10u",15u",30u".
- 3.2 Shell: Nickel plated.

4	Back-shell	1	Cold rolled steel	T=0.30mm	Nickel Plated
3	Front-shell	1	Cold rolled steel	T=0.30mm	Nickel Plated
2	Contact	4	Brass	T=0.20mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/Ivory
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO:		MATERIAL:						
MODEL NO:		FINSH:						
UNIT:	mm	SIZE:	A4	COLOR:	PART NAME:			
TOLERANCE UNSPECIFIED				USB-B TYPE SOLDER(M)				
.x		±0.3		DR: 李霞		06/05/09		
.xx		±0.20		CHK: Kevin		06/05/09		
.xxx		±0.100		APP: Kent		06/05/09		
ANG.		±1°		SCALE: 2:1		SHEET: 1 of 1		
				DWG NO:		S/A-307		
				REV:		A0		
								