

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

- Note:
- 1.Material:
- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Cold rolled steel,t=0.30mm.

- 2.Specification:
- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel plated.

3	Shell	1	Cold rolled steel	T=0.30mm	Nickel Plated
2	Contact	4	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/Ivory
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

PART NO:		MATERIAL:	
MODEL NO:		FINSH:	
UNIT:	mm	SIZE: A4	COLOR:
TOLERANCE UNSPECIFIED		DR: 李霞	PART NAME: USB-B TYPE SOLDER(M)短殼
.x	±0.3	06/05/09	
.xx	±0.20		
.xxx	±0.100		
ANG.	±1°	APPR:Kent	06/05/09
		DWG NO:	S/A-309
		SCALE:	3:1
		SHEET:	1 of 1
		REV:	A0

